

D8TURBOVZ/W

HD1080P Motorized VF Vandal Proof EXIR Dome Camera



► Camera

Image Sensor	2MP CMOS Image Sensor
Signal System	PAL / NTSC
Effective Pixels	1920(H) * 1080(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Speed	1/25 (1/30)s to 1/50,000 s
Lens	Motorized VF lens; 2.8 - 12 mm
Lens Mount	φ14
Angle Adjustment	Pan: 0°- 340°; Tilt:0°- 75°; Rotate: 0°- 355°
Day & Night	ICR
dWDR	120dB
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
S/N Ratio	More than 62dB

► General

Working Temperature/Humidity	-40 °C – 60 °C (-40 °F – 140 °F), Humidity 90% or less (non-condensing)
Power Supply	12 VDC±15%
Power Consumption	Max. 4.5W
Weather Proof Ratings	IP66
IR Range	Up to 40 m
Impact Protection	IK10.
Communication	Up the coax
Dimensions	φ145.2 × 124.1 mm (φ5.72" × 4.89")
Weight	Approx. 1600g (3.53lb)

► Menu

AGC	Support
D/N Mode	Color/BW/SMART
White Balance	ATW/ MWB
BLC	Support
Functions	Wide Dynamic Range, Digital noise reduction, Mirror, SMART IR, ATW/ MWB

► Key Features

- 2 Megapixel high-performance CMOS
- Analog HD output, up to 1080P resolution
- 2.8-12mm motorized vari-focal lens
- True Day/Night
- True WDR, up to 120dB
- EXIR technology, up to 40m IR distance
- IP66 weatherproof & vandal proof
- Up the Coax.

epcom®

Professional Video Surveillance Solutions